

# PV Disconnect 440-40-1

Box with DC Disconnect Switch and optional lightning surge protection

## ORDER INFORMATION

- **Item no.:** 19-000137    **product name:** PV Disconnect 440-40-1
- **Item no.:** 19-002120    **product name:** MNSPD-115
- **Item no.:** 19-002130    **product name:** MNSPD-300
- **Item no.:** 19-002140    **product name:** MNSPD-600

Lightning surge protectors must be ordered separately

## FEATURES

- Designed for PS150 – PS4000
- For professional installation of pumping systems



## TECHNICAL DATA

- DC rated disconnect switch enclosed
- Enclosure class IP 54
- Meets the requirements for CE

### PV Disconnect 440-20-1

Max. voltage	440 V DC
Max. current	40 A
String cable size	4 - 10 mm <sup>2</sup>
Output cable size	4 - 10 mm <sup>2</sup>

## DIMENSION/WEIGHT [mm]



Net. Weight: 1,4kg (+0,35kg)



### Optional lightning surge protector

- Connects through an existing mounting hole in the PV connect housing
- Proper grounding of the device is mandatory to achieve protection

Controller	MidNite surge protector
PS150 – PS200	MNSPD115
PS600 – PS1800	MNSPD300
PS4000	MNSPD600