

# PP200AC PowerPack

AC/DC Converter to Supply PS2-200 Pump Systems with Backup Power from a Generator or Mains Supply

## ORDER INFORMATION

- Item no.: 19-004250 / 19-004270      product name: Power Pack 200, UL

## TECHNICAL DATA

Product name	Power Pack 200	
Item no.	19-004270	19-004250
Pump System	PS2-200	
<b>AC input</b>		
Nominal voltage	120 VAC	240 VAC
Max. current	10 A	6 A
Frequency	50-60 Hz	50-60 Hz
<b>DC output</b>		
Max. voltage	48 VDC	48 VDC
Max. current	10.0 A	10.0 A

- AC input: 120/240 V ( $\pm 15\%$ ) as factory setting, 50 to 60 Hz
- DC output: max. 48 V DC (no load), 450 W
- Enclosure: steel, gasket-sealed, indoor-use, hinged front cover with key-lock
- Must be protected from direct mid-day sun
- Enclosure class: IP22
- Ambient temperature: max. 45 °C / 113°F
- PV cable length 2 m, with MC4 plugs
- Main supply AC input cable length 1.8 m, pre-connected grid main supply plugs
- Manual with further information is available on partnerNET
- Meets the requirements for CE



## DIMENSION/WEIGHT

- Packaging dimensions: 390 x 270 x 160 mm / 15.4 x 10.6 x 6.3 in
- Total weight: 6.4 kg / 14 lbs

**BERNT LORENTZ GmbH & Co. KG**  
 Siebenstuecken 24, 24558 Henstedt-Ulzburg, Germany  
 Tel +49 (0)4193 8806-700, [www.lorentz.de](http://www.lorentz.de)

**Sun. Water. Life.**

All specifications and information are given with good intent, errors are possible and products may be subject to change without notice. Pictures may differ from actual products depending on local market requirements and regulations.