

PP150AC PowerPack

AC/DC Converter to Supply PS2-150 Pump Systems with Backup Power from a Generator or Mains Supply

ORDER INFORMATION

- Item no.: 19-004240 / 19-004260 product name: Power Pack 150, UL

TECHNICAL DATA

Product name	Power Pack 150	
Item no.	19-004260	19-004240
Pump System	PS2-150	
AC input		
Nominal voltage	120 VAC	240 VAC
Max. current	10 A	6 A
Frequency	50-60 Hz	50-60 Hz
DC output		
Max. voltage	24 VDC	24 VDC
Max. current	19.0 A	19.0 A

- AC input: 120/240 V ($\pm 15\%$) as factory setting, 50 to 60 Hz
- DC output: max. 24 V DC (no load), 450 W
- Enclosure: steel, gasket-sealed, indoor-use, hinged front cover with key-lock
- Must be protected from direct mid-day sun
- Enclosure class: IP22
- Ambient temperature: max. 45 °C / 113°F
- PV cable length 2 m, with Y MC4 plugs to connect in parallel to PV-generator
- Main supply AC input cable length 1.8 m, pre-connected grid main supply plugs
- Manual with further information is available on partnerNET
- Meets the requirements for CE



DIMENSION/WEIGHT

- Packaging dimensions: 390 x 270 x 160 mm / 15.4 x 10.6 x 6.3 in
- Total weight: 6.4 kg / 14 lbs

BERNT LORENTZ GmbH & Co. KG
 Siebenstuecken 24, 24558 Henstedt-Ulzburg, Germany
 Tel +49 (0)4193 8806-700, www.lorentz.de

Sun. Water. Life.

All specifications and information are given with good intent, errors are possible and products may be subject to change without notice. Pictures may differ from actual products depending on local market requirements and regulations.